

CURRENT TRANSFORMER

Model 617
SPLIT CORE

Window Size 2.00 X 3.50

APPLICATION:
For energy management systems and instrumentation.

FREQUENCY:
50-400 Hz.

CONSTRUCTION:
The core and windings are encased in U.L. approved plastic.

INSULATION LEVEL:
0.6 kV, BIL 10 kV full wave.

CONTINUOUS THERMAL CURRENT RATING FACTOR:

1.33 at 30°C amb.,
1.0 at 55°C amb.

- Terminals are 8-32 brass studs with one flatwasher, lockwasher and regular nut.
- Flexible leads UL 1015 105°C, CSA approved, #16 AWG, 24" long are available.
- Approximate Weight: 1.2 Lbs.



REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI C57.13.
Classified by U.L. in accordance with IEC 44-1



Power Measurement Specialists
800-523-9194



This transformer is designed for assembly to an existing electrical installation without the need for dismantling the primary bus or cables.

CAUTION :

Proper safety precautions must be followed during installation by a trained electrician. Never install while bus is energized.

The current transformer must have its secondary terminals short circuited or the burden connected, before energizing the primary circuit.

CATALOG NO.	CURRENT RATIO	VA AT 1% CLASS	ANSI METERING CLASS AT 60Hz		
			B0.1	B0.2	B0.5
617-401	400:5A	1.5	2.4	4.8	—
617-501	500:5A	2.0	2.4	4.8	—
617-601	600:5A	2.5	2.4	2.4	—
617-801	800:5A	5.0	1.2	1.2	2.4
617-102	1000:5A	7.5	1.2	1.2	2.4
617-122	1200:5A	15.0	0.6	1.2	1.2